



Podiatry Association of South Africa Industrial Footwear Assessment Data Sheet



Supplier: Beier Safety Footwear	Last: Aktiv 300	Date: 02.07.2013										
Style: 30-006	Description: Atlantis	Size: UK 5 to 12										
Upper material: Buff Apollo S1	Picture: 	Last Bottom Pattern: 										
Colour ways: Black												
Lining material: Mesh												
Sock material: Wool/poron												
Unit/Heel/Sole: Strobel D/Density PU Injected/PU												
Fit description: EE medium fit												
Size marked on last		4	5	6	7	8	9	10	11	12	13	14
UK size / Dimensions (mm)												
- Insole length												
- Joint girth												
- Ball joint tread width												
- Big toe depth												
- Inside back height												
Shoe feature	Best requirement		PASA Assessment		Y/N							
Last shape/alignment	2 - 3 degrees in-flare or swing		3°		Y							
Flex at ball joint	Minimum 55 – 120 degrees against kg/cm ³ resistance, range 1.5kg to max 6 kg to size list		55° flex at 6 kg flex resistance		Y							
Location of flex area	Ball joint (forefoot tread line/flexure range)		✓		Y							
Toe clearance/Box toe	Square box toe with rounded/walled edges, extra toe allowance (adult) for tapered recedes		✓		Y							
Mid foot fit	Adjustable fixation over the mid-metatarsals, no seams over outer or inner joints		✓		Y							
Foot entry	Top line should open to mid foot to permit easy entry		✓		Y							
Heel counter	Firm support of heel (strap or closed); should not easily deform from vertical; non chafe lining, seams and heel collar		✓		Y							
Slip in Sock	Removable, washable, durable, impact cushioning equivalent to 4mm Poron		ENERGIZER OR CELESTAIR		Y							
Toe spring	Range 7mm - 12mm		7 mm		Y							
Upper material	Breathable, non deformable		✓		Y							
Lining	Breathable, non chafe, antibacterial		✓		Y							
Sole	Non slip, durable, highly flexible, firm, texture tread, double density as per Shore A chart. Ladies heel block width not less than 80% of heel seat width. Ladies wedge heels.		✓		Y							
Weight	Lightweight (as per 2012 chart per size) e.g. 800g finished size 8 Mens		790 gm		Y							
Last heel elevation	Minimal (as per chart/size 8 to 12mm to 15mm)		15 mm		Y							


Comments

Date First Approval
Signature
Annual Renewals

Must be labeled medium fit, attention to toecap position

31/07/2013 Approval Ref. No. P 763/13
 Signature: [Signature] Designation: SAPA FSC
 July 2014 [Signature] in force.

FOOTWEAR STYLE APPROVAL

	REPORT No: W47/P69/3
	PERMIT HOLDER: BEIER SAFETY FOOTWEAR
	PERMIT No: 5515/13959
BRAND NAME/TRADE MARK: BOVA AKTIV - ATLANTIS	
SPECIFICATION No: SANS/ ISO 20345	LAST No: 300

DESCRIPTION OF FOOTWEAR:
 A STYLISH LACE UP SHOE MADE UP OF FULL GRAIN PRINTED BUFFALO LEATHER.
 PADDED COLLAR AND BELLOWS TONGUE, TEXTILE VAMP AND QTR LININGS.
 DUAL DENSITY PU/PU SOLE AND COMPOSIT TOECAP.

STYLE No:	TYPE No:	SPECIAL/OPTIONAL FEATURES
30 006	BOOT	THIS SHOE HAS A SPECIAL INSOLE AND TOP SOCK WHICH HAVE PORON INSERTS TO ENSURE EXTRA COMFORT TO THE WEARER.
COMPONENTS		DESCRIPTION OF COMPONENTS
Type of Upper Material		FULL GRAIN BUFFALO APOLLO PRINT LEATHER
Type of Lining Material		TEXTILE VAMP AND QTR LININGS
Type of Stiffener		THERMO STIFFENER
Type of Soling Material		PU/PU DUAL DENSITY INJECTION MOULDED SOLE

COMMENTS:

APPROVAL:
 A CROUCAMP 